

NT573

Slow Reducer

DESCRIPTION & USES

A high quality reducer that is used in hot and cold conditions. It can be used with all the Sherwin-Williams systems including polyurethane, acid curing, pre-cat and stains. As a slow reducer in most weather conditions NT573 is only added at 5-10%.

TYPICAL CHARACTERISTICS

Colour/Odour	Clear/ Sweet Odour
Specific Gravity	0.97/ ml
Flash Point:	45°C
Boiling Point	140-150°C
1 Methoxy-2-Propyl Acetate Content	>98%
2 Methoxy-1-Propyl Acetate Content	>2%
Aromatic Hydrocarbon Content	0%

PACKAGES

NT573 Thinner is available in 200L, 20L Drums, 4L Cans and 1L Bottles.

OTHER

All instructions and recommendations are given for your guidance. Many factors beyond our control may however have an influence on the coating result. Should a problem arise, please contact us and we will help you to solve any issues.

For more information regarding this product please refer to the SDS.

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications. Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA: TWENTY TWO SERVICES P/L **Tel** (08) 9206 0220 **Fax** (08) 9206 0974
NSW: CROMA COATINGS **Tel** (02) 9533 9122 **Fax** (02) 9533 9299
VIC: CROMA COATINGS VICTORIA **Tel** (03) 9768 2312 **Fax** (03) 9768 2389
QLD: CROMA COATINGS QUEENSLAND **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

Email info@22croma.com.au
Web www.22croma.com.au