

TV4271

Polyurethane Hardener

DESCRIPTION & USES Low yellowing hardener for use in two pack polyurethane products

Compatible with: TL4371, TL4303, TF4321, TF4361, TM4060 & TH4401

Quantity available: 12.5L, 5L & 1L

TECHNICAL DATA

Density: 0,97 (+0,03) kg/l
Flashpoint: <21°C Method Closed Cup
Solid content: 25 (+1)
Storage stability: 12 months at 30°C max

NOTES This product is sensitive to humidity: keep in closed containers.
Contact us for further information

FOR INDUSTRIAL USE ONLY Data shown are mean values and cannot be construed as product specifications.
Users are advised to make their own tests to determine the suitability of products for their own purposes.

AUSTRALIAN DISTRIBUTORS FOR SHERWIN WILLIAMS

WA: TWENTY TWO SERVICES P/L **Tel** (08) 9206 0220 **Fax** (08) 9206 0974
NSW: CROMA COATINGS **Tel** (02) 9533 9122 **Fax** (02) 9533 9299
VIC: CROMA COATINGS VICTORIA **Tel** (03) 9768 2312 **Fax** (03) 9768 2389
QLD: CROMA COATINGS QUEENSLAND **Tel** (07) 3386 1000 **Fax** (07) 3386 1003

Email info@22croma.com.au
Web www.22croma.com.au