

Safety Data Sheet HY-ZINC

Supersedes Date DEC 2016 Issuing Date JUNE 2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name HY-ZINC

Recommended use Anti - corrosive zinc rich surface coating

.Corrosion inhibitor

Manufacturer, importer, supplier

NCH AUSTRALIA PTY LTD, DIV. OF NCH CORPORATION N2, 391, PARK ROAD, REGENTS PARK, NSW 2143

Telephone inquiry

+61-2-96690260 Emergency Telephone Number

+61-2-96690237/0401718972

Fax number

+61-2-96931562

Product Code 5028

Chemical nature Solvent mixture

Distributor

NCH AUSTRALIA PTY LTD, DIV. OF NCH CORPORATION N2, 391, PARK ROAD, REGENTS PARK, NSW 2143

Telephone inquiry

+61-2-96690260

Emergency Telephone Number

+61-2-96690237/0401718972

Fax number

+61-2-96931562

1-800-42

2. HAZARD IDENTIFICATION

Colour Dark Gray Physical state Liquid Odour Aromatic

Mixture or Pure Substance: Mixture

GHS

Classification

Physical Hazards

Flammable Aerosols Category 1
Gases under pressure Compressed Gas

Health Hazard

Aspiration Toxicity

Skin Corrosion/Irritation

Specific target organ systemic toxicity (single exposure)

Specific target organ toxicity (repeated exposure)

Category 2

Category 2

Other Hazards

None

Labelling

Signal Word Danger



Hazard Statements

H222 - Extremely flammable aerosol

H280 - Contains gas under pressure; may explode if heated

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary

<u>Statements</u>

P210 - Keep away from heat, sparks, open flames or hot surfaces.

P211 - Do not spray on an open flame or other ignition source

P251 - Pressurized container: Do not pierce or burn, even after use

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P261 -Avoid breathing dust/fume/gas/mist/vapours/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use in a well-ventilated area.

P280 - Wear protective gloves, protective clothing and eye protection.

P301+ P310 - IF SWALLOWED: Immediately call a physician

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P332 + P313 - If skin irritation occurs, get medical attention.

P331 - DO NOT induce vomiting

P362 - Take off contaminated clothing and wash before reuse

P314 - Get medical advice/attention if you feel unwell

P410 + P403 - Protect from sunlight. Store in a well-ventilated place

P410 + P412 - Protect from sunlight. Do not expose to temperatures

exceeding 50 °C

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents and container in accordance with applicable local regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Weight % *
Zinc	7440-66-6	30-60
Toluene	108-88-3	10-30

DIMETHYL ETHER	115-10-6	10-20
Non-hazardous mixture	-	up to 100%
Mineral spirits	64742-47-8	0-10

4. FIRST AID MEASURES

General advice Avoid breathing vapours, mist, or gas. Avoid contact with skin, eyes and clothing.

Eye Contact Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation

develops and persists.

Wipe up with absorbent material (e.g. cloth, fleece). Wash off with soap and plenty of water. **Skin Contact**

Get medical attention if irritation develops and persists. Wash contaminated clothing before

Inhalation Move to fresh air. In case of shortness of breath, give oxygen. If breathing has stopped, apply

artificial respiration. Get medical attention immediately.

Ingestion Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash Point -41 °C Method Tag closed cup

Auto ignition Temperature No information available.

Flammability Limits in Air %: Mixture. **Upper:** 10.5 Lower: 1.1

Suitable Extinguishing Media

Carbon dioxide (CO2). Dry chemical. Water spray. Foam. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Extremely flammable. Solvent vapours are heavier than air and may spread along floors. Vapors may ignite and explode. Material can create slippery conditions.

Protective Equipment and Precautions for Fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, Safe Work Australia (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Take precautionary

measures against static discharges. Remove all sources of ignition. Material can create

slippery conditions.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. **Methods for Containment**

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

Methods for Cleaning Up Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly

labelled containers.

Not applicable. **Neutralizing Agent**

7. HANDLING AND STORAGE

Keep away from open flames, hot surfaces and sources of ignition Handling

Avoid breathing vapours, mist or gas Avoid contact with skin, eyes and clothing

Keep away from heat and sources of ignition Storage

Store in original container

Keep containers tightly closed in a dry, cool and well-ventilated place

Storage Temperature Minimum 2°C Maximum 49 °C **Storage Conditions** Indoor X Outdoor Heated Refrigerated

Page 3 / 7

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ES-TWA	ISHL	ACGIH TLV	Toluene	skin notation STEL: 150 ppm STEL: 574 mg/m ³ TWA: 50 ppm	ACL: 20 ppm	TWA: 20 ppm
DIMETHYL ETHER	STEL: 500 ppm STEL: 950 mg/m³ TWA: 400 ppm TWA: 760 mg/m³	no data available	No data available		TWA: 191 mg/m³		

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Respiratory Protection

In case of insufficient ventilation wear suitable respiratory equipment When workers are

facing concentrations above the exposure limit they must use appropriate certified respirators

Eye/Face Protection

Protective gloves

Tightly fitting safety goggles.

Hand Protection Skin Protection

Wear suitable protective clothing, Impervious gloves.

General Hygiene Considerations

Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when

using this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceOpaqueColourDark Gray

Physical stateA dark grey/silver opaque liquidOdourAromatic/Hydrocarbon odour

Odour Threshold

Physical Research Contains a street of the street of th

pH No data available
Melting Point/Range No data available
Freezing Point No information available

Boiling Point/Range -25 °C
Flash Point -41 °C

MethodTag closed cupEvaporation Rate>1 (BuAc=1, >11)Vapour Pressure31mmHg @ 0 °CSolubilityNo information available.

 Vapour Density
 3.0 (Air = 1)

 Specific Gravity
 1.80-1.90

Auto ignition Temperature No information available.

Viscosity Semi- Viscous Molecular Weight No data available

Percent Volatile (Volume)

VOC Content (%)

No data available

VOC Content (g/L)

No data available

10. STABILITY AND REACTIVITY

Chemical Stability
Conditions to Avoid

Stable under normal conditions. Keep away from open flames, hot surfaces, and sources of

ignition, Temperatures above 50 °C. No materials to be especially mentioned.

No materials to be especial None under normal use.

None under normal processing.

Incompatible Products
Hazardous Decomposition Products
Possibility of Hazardous Reactions

11. TOXICOLOGICAL INFORMATION

Product Information

Principle Route of Exposure Eye contact, Skin contact, Inhalation.

The following values are calculated based on chapter 3.1 of the GHS document

Oral LD50 No information available
Permal LD50 No information available

Inhalation LC50

GasNot applicableMistnot applicableVapournot applicable

Primary Routes of Entry

Main Symptoms
Acute Effects:

Skin contact, Skin Absorption.

Eyes May cause eye irritation.

Skin Causes skin irritation. May be absorbed through the skin in harmful amounts.

Inhalation Inhalation may cause central nervous system effects. May cause central nervous system

depression. Symptoms and signs include headache, dizziness, fatique, muscular weakness,

drowsiness and in extreme cases, loss of consciousness.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Chronic Effects: May cause damage to organs through prolonged or repeated exposure if inhaled, May cause

damage to the kidneys/liver/eyes/brain/respiratory system/central nervous system if inhaled, Liver and kidney injuries may occur, Suspect reproductive hazard - contains material which

may injure unborn child.

Target Organ Effects Central nervous system, Heart, Eyes, Kidney, Liver, Respiratory system, Skin, Reproductive

System, Spleen, Adrenal gland.

Aggravated Medical Conditions Neurological disorders, Kidney disorders, Liver disorders, Respiratory disorders.

Component Information

Acute Toxicity

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Toluene	= 636 mg/kg (Rat)	= 8390 mg/kg (Rabbit	= 12.5 mg/L (Rat) 4 h	no data available	no data available
) = 12124 mg/kg (Rat	> 26700 ppm (Rat) 1		
)	h		
DIMETHYL ETHER	No information	Not applicable	= 308.5 mg/L (Rat) 4	no data available	no data available
	available		h		
Mineral spirits	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit	> 5.2 mg/L (Rat) 4 h	no data available	no data available
, i)	_ , ,		

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive	Target Organ Effects
	9			Toxicity	
Toluene	no data available	Not applicable	Х	no data available.	Skin Central nervous system Eyes Respiratory system Liver Kidney Reproductive System

Carcinogenicity

Component ES		ACGIH	ACGIH IARC		Other
Toluene	not applicable	not applicable	Group 3	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information Component Information No data available

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	log Pow
Z înc	EC50 0.11 - 0.271 mg/L Pseudokirchneriella subcapitata 96 h EC50 0.09 - 0.125 mg/L Pseudokirchneriella subcapitata 72 h	LC50 2.16 - 3.05 mg/L Pimephales promelas 96 h LC50 0.211 - 0.269 mg/L Pimephales promelas 96 h LC50 = 2.66 mg/L Pimephales promelas 96 h LC50 = 30 mg/L Cyprinus carpio 96 h LC50 = 0.45 mg/L Cyprinus carpio 96 h LC50 = 7.8 mg/L Cyprinus carpio 96 h LC50 = 3.5 mg/L Lepomis macrochirus 96 h LC50 = 0.24 mg/L Oncorhynchus mykiss 96 h LC50 = 0.41 mg/L Oncorhynchus mykiss 96 h	no data available	0.139 - 0.908: 48 h Daphnia magna mg/L EC50 Static	N/A
Toluene	EC50 > 433 mg/L Pseudokirchneriella subcapitata 96 h EC50 = 12.5 mg/L Pseudokirchneriella subcapitata 72 h	LC50 15.22 - 19.05 mg/L Pimephales promelas 96 h LC50 = 12.6 mg/L Pimephales promelas 96 h LC50 5.89 - 7.81 mg/L Oncorhynchus mykiss 96 h LC50 14.1 - 17.16 mg/L Oncorhynchus mykiss 96 h LC50 = 5.8 mg/L Oncorhynchus mykiss 96 h LC50 11.0 - 15.0 mg/L Lepomis macrochirus 96 h LC50 = 54 mg/L Oryzias latipes 96 h LC50 = 28.2 mg/L Poecilia reticulata 96 h LC50 50.87 - 70.34 mg/L Poecilia reticulata 96 h	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50	2.65
DIMETHYL ETHER	Not applicable	Oral	no data available	Not applicable	-0.18
Mineral spirits	Not applicable	LC50 = 45 mg/L Pimephales promelas 96 h LC50 = 2.2 mg/L Lepomis macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h	no data available	Not applicable	N/A

Eco toxicity effects
Persistence and Degradability
Bioaccumulation
Mobility

No information available No information available No information available No information available

13. DISPOSAL CONSIDERATIONS

Product Disposal Container Disposal

Dispose of contents/container in accordance with local regulation.

Contents under pressure. Do not puncture. Empty remaining contents. Empty containers

should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

ADG 7

UN-No UN1950
Proper Shipping Name Aerosols
Hazard Class 2.1
Haz chem Code 2YE

Description UN1950, AEROSOLS,2.1, LTD QTY

15. REGULATORY INFORMATION

Australia

Component Toluene Listed

POISON SCHEDULE Schedule 6

16. OTHER INFORMATION

Prepared By Arvind Rane
Super cedes Date DEC 2016
Issuing Date JUNE 2020

Reason for Revision List of References.GHS-SDS FORMAT
No information available.

NCH AUSTRALIA, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.