



THREADEZE ULTRA

High Temperature Anti-Seize Lubricant

- **HIGH TEMPERATURE - CONTAINS SPECIAL ADDITIVE TO WITHSTAND SUSTAINED HEAT OF UP -23°C TO 1260°C**
- **CUTS REPLACEMENT COSTS - REDUCES SEIZURE, CORROSION, PITTING, RUSTING AND GALLING OF METAL PARTS.**
- **ACTS AS A SEALANT - REDUCES FRICTION AND TIGHTENS ALL JOINTS. DOES NOT EVAPORATE, SEPARATE OR HARDEN AND FUSE TO METALS.**
- **RESIST WATER AND ACIDS - PROVIDES LONG TERM PROTECTION**
- **FOR BOTH INDOORS AND OUTDOORS APPLICATION.**

MEETS OR EXCEEDS THE SCOPE AND INTENDED USE OF MIL SPEC A-907-E

FEATURES AND BENEFITS

- Allows for easy disassembly without damaging gaskets
- Withstands sustained temperatures up to -23°C to 1260°C
- Restores threads without special equipment
- Will not harden, melt or evaporate
- Resist water washout, salt spray, steam and weathering
- Suitable for food-grade application where incidental food contact is likely.

AREAS OF USE

- Speedometer cables
- Engine fittings and fasteners
- Press fit assemblies
- Shut-off valves
- Boiler fittings
- Pins, bolts and nuts
- Studs, pipes and joints
- Cap screws and housings
- Rubber hose connections
- Brake shoes
- Clutch housings
- Studs, pipes and joints
- Cap screws and housings
- Rubber hose connections
- Brake shoes
- Clutch housings

APPLICATION

- Automotive
- Industrial plants
- Construction equipments
- Steel Mills
- Ship yards
- Schools
- Trucking firms
- Utilities
- Warehouses

TECHNICAL DATA

Base	Calcium Carbonate + zinc oxide
Temperature Range	-23°C to 1260°C
Pressure Range	Up to 3,000 psi
Does not contain	Lead, silicone or Moly

*Consult the label for full instructions and precautions before using this product. For more Technical Data, please refer to Safety Data Sheet of the product.

REMARKS: Do not use around liquid oxygen. Before applying, remove any old anti-seize compounds.



NCH AUSTRALIA PTY. LTD. (ABN 19 000 609 316)
 5-9 Ralph Street, Alexandria, NSW 2015
 T +61 2 9669 0260 F +61 2 9693 1562 www.nchaustralia.com
 ©NCH Corporation 2016

To re-order, call +61 2 9669 0260 www.nchaustralia.com

